

MySQL Access

Położenie: /etc/mysql/mysqlaccess.conf

© 3bird Projects 2005, <http://3bird.net>

```
# ----- #
# MySQLaccess version 2.0p2 #
# (c) Yves.Carlier@rug.ac.be, 1997 #
# # #
# *** Configuration file *** #
# # #
# -Default values read by mysqlaccess during initialisation. #
# This file is looked for in #
# 1) the current directory #
# 2) /etc/ #
# -Options given on the command-line override the values given in here #
# -Given options can't be overruled by empty/blanc options!! #
# ----- #
```

```
# ----- #
# Global settings #
# ----- #
```

```
$Param{'host'} = "";
$Param{'user'} = 'nobody';
$Param{'db'} = 'test';
$Param{'password'} = 'foobar';
$Param{'debug'} = 0;
```

```
# ----- #
# Settings for Command-line #
# ----- #
```

```
if ($CMD) {
  $Param{'superuser'} = 'root';
  $Param{'rhost'} = 'localhost';
  $Param{'spassword'} = "";
  $Param{'brief'} = 1;
}
```

```
# ----- #
# Settings for CGI-BIN #
# ----- #
```

```
if ($CGI) {
  $Param{'superuser'} = 'root';
  $Param{'rhost'} = 'localhost';
  $Param{'spassword'} = "";
  $Param{'table'} = 1;
}
```

```
1; #to make require happy
```

Ostatnia aktualizacja: 22 sierpień 2005.