

# MySQL - plik konfiguracyjny

Położenie: /etc/mysql/my.cnf

© 3bird Projects 2005, <http://3bird.net>

```
# /etc/mysql/my.cnf: The global mysql configuration file.
# $Header: /home/cvsroot/gentoo-x86/dev-db/mysql/files/my.cnf,v 1.3 2002/05/04 01:58:36 woodchip Exp $
# This file can be simultaneously placed in three places:
# 1. /etc/mysql/my.cnf to set global options.
# 2. /var/lib/mysql/my.cnf to set server-specific options.
# 3. ~/.my.cnf to set user-specific options.
# One can use all long options that the program supports.
# Run the program with --help to get a list of them.
# The following values assume you have at least 32M RAM!
```

## [client]

```
#password      =      my_password
port           =      3306
socket         =      /var/run/mysqld/mysqld.sock
```

## [safe\_mysqld]

```
err-log        =      /var/log/mysql/mysql.err
```

## [mysqld]

```
#skip-networking
skip-innodb
user           =      mysql
pid-file       =      /var/run/mysqld/mysqld.pid
socket         =      /var/run/mysqld/mysqld.sock
port          =      3306
log            =      /var/log/mysql/mysql.log
basedir        =      /usr
datadir        =      /var/lib/mysql
tmpdir         =      /tmp
language       =      /usr/share/mysql/english
skip-locking
set-variable   =      key_buffer=16M
set-variable   =      max_allowed_packet=1M
set-variable   =      thread_stack=128K
```

## [mysqldump]

```
quick
set-variable   =      max_allowed_packet=1M
```

## [mysql]

```
#no-auto-rehash # faster start of mysql but no tab completion
```

## [isamchk]

```
set-variable   =      key_buffer=16M
```

Ostatnia aktualizacja: 22 sierpień 2005.

