

Xft - plik konfiguracyjny

Położenie: /etc/X11/XftConfig

© 3bird.net 2005, <http://3bird.net>

```
# XftConfig
# Use with Type1 and TrueType fonts. Note that each application scans all these directories during startup, so you may want to disable
some to get better speed.

# Standard XFree86 Type 1 fonts
dir "/usr/X11R6/lib/X11/fonts/Type1"
# TTF fonts
dir "/usr/X11R6/lib/X11/fonts/truetype"
dir "/usr/X11R6/lib/X11/fonts/TTF"
# URW fonts
dir "/usr/share/fonts/default/Type1"

# alias 'fixed' for 'mono'
match any family == "fixed"      edit family += "mono";

# Check users config file
includeif "~/.xftconfig"

# Substitute TrueType fonts for Type1 versions
match any family == "Times"      edit family += "Times New Roman";
match any family == "Helvetica"  edit family += "Verdana";
match any family == "Courier"    edit family += "Courier New";

# Use TrueType fonts for defaults
match any family == "serif"      edit family += "Times New Roman";
match any family == "sans"       edit family += "Arial";
match any family == "sans"       edit family += "Verdana";

# Use monotype.com (andale) face where possible
match
    any family == "mono"
    all slant == roman
    all weight < bold
edit
    family += "monotype.com";

# otherwise, use courier
match any family == "mono"      edit family += "Courier New";
match any family == "mono"      edit family += "Courier";

# Alias between XLFD families and font file family name, prefer local fonts
match any family == "Charter"    edit family += "Bitstream Charter";
match any family == "Bitstream Charter" edit family += "Charter";
match any family == "Lucidux Serif" edit family += "LuciduxSerif";
match any family == "LuciduxSerif" edit family += "Lucidux Serif";
match any family == "Lucidux Sans" edit family += "LuciduxSans";
match any family == "LuciduxSans" edit family += "Lucidux Sans";
match any family == "Lucidux Mono" edit family += "LuciduxMono";
match any family == "LuciduxMono" edit family += "Lucidux Mono";
```

```

# TrueType font aliases
match any family == "Comic Sans"    edit family += "Comic Sans MS";
match any family == "Comic Sans MS" edit family =+ "Comic Sans";
match any family == "Trebuchet"    edit family += "Trebuchet MS";
match any family == "Trebuchet MS" edit family =+ "Trebuchet";
match any family == "Monotype"      edit family =+ "Monotype.com";
match any family == "Andale Mono"   edit family += "Monotype.com";
match any family == "Monotype.com"  edit family =+ "Andale Mono";

# modifications from Laurent Culioli
match
    any family == "webdings"
        edit antialias = false;
        encoding += "glyphs-fontspecific";
match
    any family == "wingdings"
        edit antialias = false;
        encoding += "glyphs-fontspecific";

# a nice default for sans serif (same as used in yudit)
match any family == "sans"    edit family =+ "Arial";
match any family == "sans"    edit family =+ "MS Gothic";
match any family == "sans"    edit family =+ "Gulim";
match any family == "sans"    edit family =+ "Baekmuk unigulir";
match any family == "sans"    edit family =+ "Lucida Sans Unicode";
match any family == "sans"    edit family =+ "Tahoma";
match any family == "sans"    edit family =+ "BPG UTF8 M";
match any family == "sans"    edit family =+ "GF Zemen Unicode";
match any family == "sans"    edit family =+ "MS Mincho";
match any family == "sans"    edit family =+ "Pigiarniq";
match any family == "sans"    edit family =+ "Urdu Naqsh Nastalique";
match any family == "sans"    edit family =+ "Ballymun RO";
# a nice monospaced one
match any family == "mono"    edit family =+ "Lucida Console";

# If the Microsoft Web Fonts are not installed, we have to find a replacement these come with Sun JDK 1.3
match any family == "Verdana"    edit family =+ "Lucida Sans";
match any family == "Times New Roman" edit family =+ "Lucida Bright";
match any family == "Courier New"  edit family =+ "Lucida Sans Typewriter";

# URW fonts
match any family == "Verdana"    edit family =+ "Nimbus Sans L";
match any family == "Times New Roman" edit family =+ "Nimbus Roman No9 L";
match any family == "Courier New"  edit family =+ "Nimbus Mono L";

# XFree86 default fonts
match any family == "Verdana"    edit family =+ "LuciduxSans";
match any family == "Times New Roman" edit family =+ "LuciduxSerif";

# last ressort defaults
match any family == "Courier"    edit family =+ "mono";
match any family == "Helvetica"  edit family =+ "sans";
match any family == "Arial"      edit family =+ "sans";
match any family == "serif"      edit family =+ "sans";
match any family == "Times"      edit family =+ "serif";

```

Aditions from Danny Tholen

match

any family == "symbol"

edit

antialias = false;

encoding += "glyphs-fontspecific";

match

any family == "Standard Symbols L"

edit

antialias = false;

encoding += "glyphs-fontspecific";

match

any family == "dingbats"

edit

antialias = false;

encoding += "glyphs-fontspecific";

match

any family == "Cursor"

edit

antialias = false;

encoding += "glyphs-fontspecific";

match

any family == "StarBats"

edit

antialias = false;

encoding += "glyphs-fontspecific";

match

any family == "StarMath"

edit

antialias = false;

encoding += "glyphs-fontspecific";

Ostatnia aktualizacja: 18 maj 2006.